



About Relic
Relic acts like a component manufacturer that is focused on premium quality and precise products, reliable, strong and faithful remained to reputation. What we considered are the most dependable and time-consuming technology within the industries cooperation. Besides, Relic attempts the ODM and OEM fields for best servicing to our great customers.

We were pioneering of presenting extremely light in weights without any else strengths loss. Although the materials cost is unlimitedly raised, Relic still insists all the time on manipulation of materials to yield lighter and stronger components.

Combining metallurgic technologies and aesthetics in the field, Relic is rich in the expertise at ODM and OEM experiences for our worldwide customers in wide range products. In the great knowledge and professional of components, Relic always follows the trendy and keeps in mind, doing everything reliable to meet perfection wherever innovative designs and technologies related to our collections.

Relic Your Ride



RELIC
INTERNATIONAL INC.
E-mail : info@relicmtb.com



DESIGN FOR HIGH PERFORMANCE

www.relicmtb.com




40T/42T+16T SPROCKET

Material: AL7075 T6 CNC machined
Teeth: 16T(23g)/40T(72g)/42T(78g)
Color: Gold (16T) Blue, Green, Red (40T/42T)

A larger cassette with 16T & 40T/42T sprockets adopted to upgrade 10-speed system, instead of 11T and 17T, the 16T is smoother as shifting, 40T/42T enclosed after 11T-36T cassette is also compatible with Shimano 10 spd drivetrain system, it is easy for installation, great durability, and the best gear ratio arranged.




SPEAR STEM

Material: Alloy 6061 CNC machined
Barrow: Φ 31.5mm
Extension: 70mm / 90mm
Angle: 5°
Super Lightweight: 140g
Color: Gold, Red, Blue

XC/AM Lightweight Stem Fully CNC machined from top to bottom, and race proven angle and extension.




32T/34T X-CHAINRINGS

Material: AL7075 T6 CNC machined
Compatible with MTB cranksets BCD 104mm
Weight: 32T (49 g), 36T (77 g)
Color: Black

The CNC machined and narrow-wide designed chainring with AL7075 T6, available in 2 sizes: 32T and 36T, compatible with 9 & 10 speed chains.




FRO PEDAL

Material: Alloy 6061 T6
Platform: 104mm x 100mm
Thickness: 18mm
Weight: 389g/ pair
Color: Black, Blue, Red

The delicate CNC cutting appearance comes with FRO Pedal, with DU sealed bearing and cr-moly axle, there are also 10pcs replaceable steel traction pin on each side of FRO Pedal.



10 to 1 SINGLE SPEED KIT

Fits any Shimano compatible 8, 9, 10 or 11 speed hub. Convert 10 speeds cassette into single speed. Easily adjust the chain line by the spacers arranging on the cassette (drive shell). The 10 to 1 single speed kit include 2 spacers, 1 lock ring (38mm), a washer and 16T & 18T sprocket, color available in black and red.

Kit includes:

2 stainless steel sprocket (16T & 18T), 2 aluminum spacers, 1 aluminum lock ring (12T/38mm), 1 washer



LOCK RING 11T/12T

The Aluminum Lock Ring applied in Shimano cassettes with 11T (35mm) and 12T(38mm) sprocket.

Weight: 4.5g(11T)/ 5g(12T)

Color: Black, Blue, Orange, Red



TELESCOPING POST C CLAMP

The anodized Relic Seat Clamp for telescoping post is easily to position to hold the seatpost and guide the floppy cable.

Material: AL6061 T6

Size: 31.8mm & 34.9mm

Seat Clamp weight: 24g

QR Seat Clamp weight: 34g

Color: Black



Bolt on



CARBON FORK EXPANDER PLUG

Machined aluminum expander for use as an internal headset preloads plug on the carbon steerer forks. The cr-moly expander bolt and 32mm length could accept standard stem and preload bolt and on top-cap.

Material: AL6061 T6

Length: 32mm

OD: 22-26mm

Weight: 47g

Size: 1-1/8"

Color: Black



CG-C CHAINGUIDE

Mount clamp Band Chainguide, protect the chain to be offset, single speed especially apply at XX1 narrow-wide chainwheel.

Full CNC machined

Size: 34.9mm

Weight: 47g

Color: Black

CG-E2 CHAINGUIDE

E2 Mount Chainguide, for E2 direct mount, simple and easy setting for narrow-wide chainring, make it work stable and more effective.

Full CNC machined

Size: 34.9mm

ChainRing Capacity: 28T-42T

Weight: 38g

Color: Black



160/180/203mm ROTOR

The Aluminum core reduces braking heat as the steel outer segment provides the solid stopping power and a durable braking surface.

OD/Weight: 160mm(128g)/180mm(164g)/203mm(228g)

Color: Black



DISC BRAKE ADAPTORS

The various adaptors are designed for fitting International Standard (IS) mount or Post Mount (PM) calipers on the frame and the fork tabs.

Rotor OD: 140/160/180/203mm

Color: Black



QR-MTB

Lightness alloy 6061-T6, anodize lever with brass spacer for easy turning, CNC machined Quick Release and Cr-moly axle that make the best performance for stable wheelset.

Length: 100mm (front)/135mm (rear)

Weight: 68g/pair

Color: Black, Green, Red



GP-F COMBO MOUNT

The combo mount of Garmin & GoPro on the handlebar holds your action camera out of the way, out of sight and centered on the handlebar to have good view with speed your ride.

Material: AL6061 T6

Weight: 72g (w/o adaptor)

Color: Black

Clamp: ø31.8mm handlebar with ø25.4mm & 22.2 shim

Front & Rear Mount, 2pcs/pack, install either GoPro on the front mount of handlebar or the rear mount of the rail of saddle, wherever you prefer setting up, the pack will be your best option for landscape riding.



PRO-F MOUNT

(Front Mount)

Compatible for GoPro

Material: AL6061 T6

Clamp: ø31.8mm handlebar

with ø25.4mm & 22.2 shim

Weight: 38g (w/o adaptor)

Color: Black



Not include GoPro.

PRO-R MOUNT

(Rear Mount)

Compatible for GoPro

Material: AL6061 T6

Saddle rail: 7mm

Weight: 47.5g

Color: Black

